



ALARM & SECURITY CABLE (For European Standard)

MULTICONDUCTOR - FOIL SHIELDED AND UNSHIELDED RISER-RATED PVC

ALH PVC / LSOH - 300/300V

Part No.	Specification	Cond. (mm)	Insulation (mm)	Outer Dia. (MM)
P83210	2x0.22	7x0.20	0.23	3.3
P83220	4x0.22	7x0.20	0.23	3.5
P83222	6x0.22	7x0.20	0.23	4.2
P83224	8x0.22	7x0.20	0.23	4.6
P83226	10x0.22	7x0.20	0.23	5.2
P83228	12x0.22	7x0.20	0.30/0.23	5.4
P83230	2x0.22+2x0.50	7x0.20	0.30/0.23	4.1
P83232	4x0.22+2x0.50	7x0.20	0.30/0.23	4.4
P83234	6x0.22+2x0.50	7x0.20	0.30/0.23	5.2
P83236	8x0.22+2x0.50	7x0.20	0.30/0.23	5.4
P83238	10x0.22+2x0.50	7x0.20	0.30/0.23	5.8
P83240	12x0.22+2x0.50	7x0.20	0.30/0.23	5.9
P83242	14x0.22+2x0.50	7x0.20	0.30/0.23	6.3
P83244	16x0.22+2x0.50	7x0.20	0.30/0.23	6.6
P83246	20x0.22+2x0.50	7x0.20	0.30/0.23	7.1
P83248	2x0.22+2x0.75	7x0.20	0.35/0.23	4.8
P83250	4x0.22+2x0.75	7x0.20	0.35/0.23	5.0
P83252	6x0.22+2x0.75	7x0.20	0.35/0.23	5.4
P83254	8x0.22+2x0.75	7x0.20	0.35/0.23	5.8
P83256	10x0.22+2x0.75	7x0.20	0.35/0.23	6.2
P83258	12x0.22+2x0.75	7x0.20	0.35/0.23	6.4
P83260	14x0.22+2x0.75	7x0.20	0.35/0.23	6.6
P83262	20x0.22+2x0.75	7x0.20	0.35/0.23	7.8



Application:

Security and Alarm Systems, Intercom/Public Address Systems

Conductor:

Stranded CCA or Bare Copper or Tinned Copper

Insulation:

Color-Coded PVC

Shield:

Aluminum-Polyester Foil (100% Coverage)

Sheath:

White PVC

Stranded BC or TC Drain Wire

Temperature Range:

In motion -10°C till +70°C

*All items can be made with LSOH material which is fire-resistant.

*Other cable items with customer specification are available on demand.



FIRE ALARM CABLE (For European Standard)

PVC Insulation, Multicores, Layers, Collective Screen

Part No.	Specification	Conductor Resistance Ohm/km	Test Volt. V c.c.s	Operating Volt. V	Temperature Range °C
O90050	2x0.50	39	2500	250	-10 / +80
O90060	2x0.75	26	2500	250	-10 / +80
O90070	2x1.00	19.5	2500	250	-10 / +80
O90080	2x1.50	13.3	2500	250	-10 / +80
O90090	2x2.50	7.98	2500	250	-10 / +80

Application:

Communication and signaling in Fire alarm systems

Conductor:

Stranded Pure Red Copper

Insulation:

Polyvinylchloride rated

Shield:

Collective Screen of Aluminum/Polyester Foil BC or TC Drain Wire wrapped by Polyester Tapes

Sheath:

Flame retardant polyvinylchloride (RED Colour) or any other colors

Temperature range:

In motion -10°C till +80°C

Standard Packing:

Coils 100M or 500M

*Other cable items with customer specification are available on demand.

